

High-Tech Charging for Two Batteries!



**NIMH/NICD
AND LIPO/LIFE
COMPATIBLE**

**1-6S LIPO/LIFE
1-16 CELLS
NIMH/NICD**

**CHARGE &
DISCHARGE
2 BATTERIES**

**UP TO 20A
CHARGE
CURRENT**

**10 MEMORY
PROFILES**

**EASY
STORAGE**

**INTEGRATED
BALANCER**

The Team Orion Advantage TwinSpec Charger features the Advanced Twin Charge System which allows the simultaneous charge or discharge of two batteries with currents of up to 20A!

Team Orion's TwinSpec charger has two individual channels which can be setup and used independently one from another. This means that you can charge a LiPo battery on one channel and a NiMH battery on the other one. You can also charge a battery on one channel and discharge another battery on the other channel, all at the same time. During use you can easily switch from one channel to another, just by pressing a key. This is flexibility of use! The Advantage TwinSpec charger can charge and discharge LiPo/LiFe/NiMH/NiCd batteries with a current of up to 20A for charging and 10A for discharging. For safe LiPo and LiFe charging, the charger is equipped with an integrated balancer for each channel. There is a storage charge mode which prepares

the batteries for storage, a cycling mode and discharge mode. The charger is also equipped with temperature probes which allow you to monitor the batteries temperature. About every parameter is adjustable and all the charge and discharge data is automatically stored for later review.

The Advantage TwinSpec is the ideal charger for the enthusiast who wants the best that technology can offer.



- Microprocessor controlled dual charger for NiMH, NiCd, LiPO & LiFe
- 1 to 16 cells NiMH/NiCd - 1 to 6 cells LiPo/LiFe
- Charge or discharge two batteries simultaneously
- Two independent channels
- Linear charge current up to 20A
- Discharge up to 10A
- Integrated balancer
- Charge and discharge data storage for later review
- Storage charge function
- Cycling mode
- Adjustable automatic delta-peak charge cutoff
- Adjustable max peak voltage
- Adjustable discharge cut-off
- Adjustable max charged capacity
- Temperature monitoring and cut-off
- Easy to read, blue backlit LCD display
- Robust metal case
- Practical keypad
- Detailed instructions


Designed for...




LiPo/LiFe 1-6 cells
NiMH/NiCd 1-16 cells



Glow plug
igniters



Transmitters



Receiver packs

Product details

Input voltage : 10-15V
Cell type (per channel): NiMH / NiCd, 1-16 cells, LiPo/LiFe 1-6 cells
Charge current : 0.1A to 20A
Discharge current : 0.1A to 10A
Dimensions : 160x159x53mm
Weight : 1270g
Part N° : ORI30153