

ULTIMA RB6

SET UP SHEET



Name ELLIOTT BOOTS Date 25-5-2013 Truck / City EDEN PARK Event RD 3 NATIONAL

Front Suspension

4.8mm Ball Stud: Camber: \circ

UM128 (Std)

UMW508 (+2mm High Mount)

Upper Spacer: 2 mm

4.8mm Ball Stud Spacer: \circ mm

Axle Spacer: Out ___ mm In ___ mm

Wheel Hub: ___ mm

4.8mm Ball Stud: LA246 (-1mm Low Mount) UM129 (Std)

Ackerman Steer Spacer: \circ mm

Bump Steer Spacer: \circ mm

Toe: In Out ___ \circ

Caster: 25 \circ 30 \circ

Spacer: 0.5 1.0 None

Caster Block: 0 \circ 2 \circ 4 \circ

Block position: IN OUT

Axle Height Spacer: 1 mm 2.5 mm

Front Bulkhead Weight Placement: None Bulkhead Inside ___ oz ___ g On the skid plate ___ oz ___ g * 1oz=28g

Comments: _____

Wheelbase: F: 1 mm R: 1 mm

Rear Suspension

Sus Holder Spacer: F 0.5 1.0 None R 0.5 1.0 None

Anti-Squat: \circ

4.8mm Ball Stud: UM129 (Std) UMW508 (+2mm High Mount) 97050M

Sway Bar: None ___ mm

Camber: 2 \circ

Upper Spacer: 2 mm

Wheelbase: F: 2 mm R: \circ mm

RR: Upper Spacer: ___ mm

Mid: Lower Sus Holder: Normal Aluminum (Opt) RF UMW511+UMW512 RF2 UMW514+UMW515

Wide RF2 UMW514+UMW515

Motor Position: Rear Motor Midship Motor

Diff.: Gear Diff. # _____ Ball Diff.

Comments: _____

Shock

	Front	Rear
Shock Piston:	<u>KIT</u>	<u>KIT</u>
Shock Oil:	# <u>35</u>	# <u>2.5</u>
Shock Spring:	<u>RED</u>	<u>RED</u>
Limiters:	in ___ mm out ___ mm	in ___ mm out ___ mm
Shock Length(A):	___ mm	___ mm
Shock Length(B):	___ mm	___ mm
Shock Length(C):	___ mm	___ mm
Ball End type:	Front: <input checked="" type="checkbox"/> S <input checked="" type="checkbox"/> M <input type="checkbox"/> L	Rear: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L

Chassis

Screw:

Ride Height: F 18 mm R 18 mm

Battery Position

Battery Type: Straight Separate Short

Battery Placement: Front Rear

Truck Condition

Smooth Bumpy Low Truaction Med. Truaction Higt Truaction Wet Dry

Sandy Soft Dirt Grass Blue Groore Clay Dusty Other

Wing

Wing Mount: Blast-S Blast-L Step-S Step-M Step-L Step 2.0

Wing Angle: Narrow Wide 4 \circ 7 \circ 10 \circ

Lip: _____

Tire

Front: SCH SPINES

Rear: ANSWER

Wheel: KYOSHO

Traction Compound: YELLOW.

Electronics

Motor: LRP x 20 7.5

Pinion/Spur: 23/76

Battery: LRP

ESC: LRP FLOW.

Comment

B. FINAL

LAZER ZX-5FS

SET UP SHEET



Name: ELLIOTT BOOTS Date: 26/5/2013 Track: EDEN PARK / NATIONAL Event: RDV 3 NATIONAL

Front Suspension

Shock stay hight: _____ mm

Spacer: 2 mm

Shock Stay:
 LA216B(SP)
 LA216HB

Ride Height: 18 mm

Camber Angle: 1 °
Toe Angle: _____ °
Sway Bar: 1/2

Front Diff:
 Rigid
 Oneway
 Differential, Setting: MED

Sus. Holder Spacer:
 Front
 Rear

Spacer: 0 mm

Bump Steer Spacer: 0 mm

Caster Block:
 7°
 10°

Axle-Height Spacer: Up Down

Bellcrank Spacer: 1 mm

Rear Suspension

Shock stay hight: 2 mm

Spacer: 2 mm

Shock Stay:
 LA217(SP)
 LA217H

Wing Height: _____ mm

Camber Angle: 2 °

Sway Bar: 1.2

Sus. Holder(RF):
 IN OUT

Sus. Holder(RR):
 IN OUT

Ride Height: 19 mm

Sus. Holder Spacer:
 Front
 Rear

Wheel Spacer: _____ mm

Hub Spacer:
 F: 2 mm
 R: 0 mm

Rear Sus. Arm:
 LA272(UM566,UM521)(SP)
 UM521-1(1-Hole)
 LA255

Rear Hub and Toe:
 0°Type-B(UM519)
 0°Type-B2(UM516-2)
 0°Alu(UMW516-0)
 0.5°Alu(UMW516-05)
 1°Alu(UMW516-1)

Shock

Shock Piston: Front KIT Rear KIT

Shock Oil: # 37.5 # 27.5

Shock Spring: RED GOLD

Limiters: in mm out mm in mm out mm

Shock Length(A): _____ mm

Shock Top Type:

Std:RB5 Low:ZX5FS Std:RB5 Low:ZX5FS

5.8mm Ball End:
 Front: S M L
 Rear: S M L

Tire

Tire: Front SCH SPIKE Rear SCH SPIKE

Inserts: ANSWER ANSWER

Wheel: KYOSHO KYOSHO

Traction Compound: YELLOW

Body/Wing/Other

Body: STD

Wing: STD

Lip hight: _____

Wing Angle: 4° 7° 10°

Battery Post: Pla Alu

Slipper Type:
 Direct
 Separates

Slipper Sheet(F-R):
 Red-White
 Red-Red
 White-White

Center Post:
 Pla Alu

Back bone screw:
 F R

Comments

5TH OVERALL

Electronics

Motor: LRP X 20

Pinion/Spur: 19/78

Battery: LRP

ESC: LRP FLOW

Radio: SANWAR

Servo: SANWAR

Throttle/Brake: _____

EPA: _____ **Expo:** _____

Initial brake: _____

Drag brake: _____

Throttle profile: _____

Steering expo: _____

Steering speed: _____

- | | |
|---|---|
| <input type="checkbox"/> Smooth | <input type="checkbox"/> Sandy |
| <input checked="" type="checkbox"/> Bumpy | <input type="checkbox"/> Soft Dirt |
| <input type="checkbox"/> Low Traction | <input type="checkbox"/> Grass |
| <input type="checkbox"/> Med. Traction | <input type="checkbox"/> wet |
| <input checked="" type="checkbox"/> Higt Traction | <input checked="" type="checkbox"/> Dry |
| <input type="checkbox"/> Blue Groove | <input type="checkbox"/> Dusty |
| <input type="checkbox"/> Clay | <input type="checkbox"/> Other |

Kind in spring

Soft ↑	Pink
	White
	Gold
	Red
	Yellow
	Orange
Hard ↓	Green

Sway Bar

1.0	White
1.1	Pink
1.2	Red
1.3	Orange
1.4	Yellow
1.5	Blue
1.6	Green