

LAZER ZX6 SET UP SHEET



Name ELLIOTT BOOTS Date 9.11.2014. Truck / City MARITIME Event NORD CUP.

Front Suspension:

Shock Position:

Lower Sus Holder Block:
Front B Rear B

Lower Sus Holder Spacer:
Front 0 mm Rear 1 mm

Comments:

Upper Arm Position:

4.8mm Ball Stud:
 97050M(Std)
 UM129

Upper Spacer: 0 mm

Camber 0°

Spacer: 0 mm

Axle-Height Spacer:
 Up
 Down

Caster Block:
 7°
 10°

Shock Position:

Wheelbase:
Front 1 mm
Rear 1 mm

Bump Steer Spacer: 0 mm

Toe:
 In
 Out

Sway Bar:
 None
 1.3 mm

Ackerman Spacer: 0 mm

Front Diff:

Gear Diff. # _____
 Ball Diff.

Rear Suspension:

Shock Position:

Wing Stay Position:

Lower Sus Holder Block:
Front D Rear C

Lower Sus Holder Spacer:
Front 4 mm Rear 2 mm

Comments: 32g WEIGHT MIDDLE

Upper Arm Position:

4.8mm Ball Stud:
 97050M(Std)
 UM129

Upper Spacer: 0 mm

Sus. Arm:
 LA272(Std)
 UM713

Camber _____

Hub Carrier:
 Type-B (UM519)
 Type-B2 (UM519-2)

Upper Spacer: 2 mm

Shock Position:

Wheelbase:
Front: 4 mm
Rear: 0 mm

Toe In: 2.5°

Slipper Type:

Separates
 Direct

Sway Bar:
 None
 _____ mm

Rear Diff:

Gear Diff. # _____
 Ball Diff.

Shock:

	Front	Rear
Shock Piston:	<u>1.6 X 2</u>	<u>1.7 X 2</u>
Shock Oil:	# <u>60</u>	# <u>40</u>
Shock Spring:	<u>ORANGE</u>	<u>GOLD.</u>
Limiters:	in _____ mm out _____ mm	in _____ mm out _____ mm
Shock Length(A):	_____ mm	_____ mm
Shock Top Type:	<input checked="" type="checkbox"/> Alu(UM719/Std)	<input type="checkbox"/> UM753-1
5.8mm Ball End:	Front: <input checked="" type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L Rear: <input checked="" type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L	

Chassis:

Ride Height:

Front 18 mm Rear A B 17 mm

Tire: Front _____ Rear _____

Tire: SCHUMACHER

Inserts: MINI PINS

Wheel: YELLOW.

Traction Compound: _____

Electronics:

Battery: Saddle Pack
 Short

Motor Position: Front
 Rear

Servo Mounting: Straight
 Sideways

Motor: TEKIN 6.5

Motor Timing: 0

Pinion/Spur: 23/STD.

ESC: TEKIN RSX

Radio: SANWA Z

Servo: SANWA.

Body / Wing:

Body: STD.

Wing Mount: Narrow Wide

Wing Dum Height: _____ mm

Wing: RUDEBITS

Wing Angle: 4° 7° 10°

Lip Height: _____ mm

Material:

Screw: Steel Titanium

Pinion Gear: Steel Aluminium

Shock O-Ring: O-ring X-ring Red Clear

Comment: NO BLADDERS.
RDR WING MOUNT.
RUDEBITS REAR WING.
RUDEBITS 32g Weight Middle
Chassis.

Name: ELLIOTT BOOTS Date: 9.11.2014 Track / City: MARITIME. Event: World Cup.

Front Suspension

Upper Spacer: _____ mm
 Front Tower: Std Carbon
 Toe: In Out 1°
 Tie Rod: _____
 Front Bulkhead Weight Placement: None Bulkhead Inside BRASS. oz _____ g On the skid plate _____ oz _____ g * 1oz=28g
 4.8mm Ball Stud: UM128(Std) UMW508(+2mm High Mount)
 Camber: _____ °
 Axle Spacer: Out _____ mm In _____ mm
 Wheel Hub: _____ mm
 Front Axle: UM569 (Std) UM506 (RB5)
 Caster Block position: IN (wide/Std) OUT (Narrow)
 Axle Height Spacer: 0.5 mm 1 mm
 Ackerman Steer Spacer: _____ mm
 C Hub: Std Carbon
 Knuckle: Std Carbon
 Bump Steer Spacer: _____ mm
 Caster: 25° 30°
 Spacer: 0.5 1.0 None
 Caster Block: 0° 2° 4°
 Front Arm: Std Carbon
 *Comments: KYOSHO BRASS WEIGHT. Wheelbase: F: 1 mm R: 0 mm

Rear Suspension

Rear Tower: Std Carbon
 Upper Spacer: _____ mm
 Hub spacing: F: 0 mm R: 2 mm
 Outer Bearing: 5X10 5X11 5X13
 Wheelbase(arm): F: _____ mm R: _____ mm
 Rear Arm: UM713(Std) UM521/566 UM521-1 UM503(Short) UMW711(Carbon)
 Rear Hub Toe: 0° Type-B(UM519Std) 0° Type-B2(UM519-2) 0° Alu (UMW704-0) 0.5° Alu (UMW704-05) 1° Alu (UMW704-1)
 Sus Holder Spacer: F 0.5 1.0 None R 0.5 1.0 None
 Anti-Squat: _____ °
 4.8mm Ball Stud: UM129 UMW508(+2 High mount) 97050M UM128(Std)
 Sway Bar: None _____ mm
 Camber: -2°
 Axle Spacer: Out _____ mm In 2 mm
 Universal Swing Shaft: _____
 RR: _____
 Lower Sus Holder: _____ mm
 Normal Aluminum(Opt)
 Narrow RF UMW511+UMW512 RM UMW705/706
 Wide RF2 UMW514+UMW515 MM UMW705/707
 Motor Position: Rear Motor Midship Motor
 Diff.: Gear Diff. # _____ Ball Diff.
 Comments: _____

Shock

Shock Piston: Front STD Rear STD
 Shock Oil: # 40 # 32.5
 Shock Spring: GOLD RED
 Limiters: in out mm in out mm
 Shock Length(A): _____ mm _____ mm
 Shock Length(B): 21.5 mm 28.3 mm
 O-ring: _____
 Ball End type: Front: S M L O
 Rear: S M L O
 Shock Cap: UM719(Std) UM753-1(Bleeder)

Battery Placement:

Comments: RUBER ITS BRASS TRAY UNDER BATT.
 Battery Placement: UM787 None Screw
 Foam: Front Rear None

Chassis

Chassis: UM700(Std) UMW720(Lightweight)

 F 18 mm Ride Height: R 18 mm

Battery Type

Straight Saddle Short
 Type: LRP

Other

Motor: TEKIN 7.5
 ESC: RSX TEKIN
 Pinion/Spur: 26/78

Track Condition

Smooth Sandy Bumpy Soft Dirt Low Bite Grass Med. Bite Blue Groove High Bite Clay Wet Dusty Dry Other

Body&Wing

UMB03 UMB03LW
 Blast-S Blast-L Step-S Step-M Step-L Step 2.0
 Lip: R1.
 Narrow Wide
 Wing Mount: Narrow Wide
 Wing Angle: 4° 7° 10°

Tire

Tire: Front STAGGER Rear Mini Traction Compound and/or comments: SCHUMACHER YELLOW.
 Inserts: RIB PINS
 Wheel: _____

Comments:

RDRP - Front & Rear Aluminum Bulkheads.
RDRP - Wing Mounts.
PROLINE PHANTOM SHELL.